

Specifications - Engineered Strand Bamboo Collection

Products:				All products listed are FSC certified.
Carbonized	(FRE-OS14-142C)	* Coconut	(FRE-OS15-189-CO)	
Natural	(FRE-OS14-142N)	* Husk	(FRE-OS15-189-Husk)	
Island	(FRE-OS14-142ISL)	* Java	(FRE-OS15-189-Java)	
		* Seashell	(FRE-OS15-189-Sea)	
Dimension & Structure:				
	Product size	14 x 142 x 1850mm (9/16" x 5 5/8" x RL to 72 7/8") *14 x 189 x 1850mm (5/8" x 7 7/16" x RL to 72 7/8")		
	Product Type	Engineered 3-Ply construction Tongue and Groove, End matched		
	Face Layer Thickness	3mm (1/8")		
	3-Layer Platform	11mm (7/16")		
	Face Layer Type	Smooth Face Brushed / Bleed for Island only		
	Edge Preparation	0.25mm micro-bevel		
Species:				
	Face Layer Species	Strand Bamboo		
	3-Layer Platform	Poplar		
	Moisture Content	6-8%		
Adhesive/Finish:				
	Adhesive	CARB Phase 2 Compliant		
	Coating Type	U.V. cured water based polyurethane		
	Surface Type	Closed pores		
	Glossiness Factor	40 ± 5 semi-gloss finish		
Packaging:				
	Square Feet per Carton	22.59 sq. ft(2.10 m ²) *30.07 sq. ft(2.80 m ²)		
	Carton s per Pallet	48 * 40		
	Square Feet per Pallet	1,084.32 sq. ft (100.87 m ²) * 1202.8 sq. ft (111.89 m ²)		
	Weight per Carton	42 lbs. (19 kg) *53 lbs (24 kg)		
	Weight per Pallet	2,060 lbs. (940 kg) *2120 lbs (960 kg)		
	Pallets per 20' Container	12		
	Pallets per 40' Container	24		